

CORRECTED VERSION

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
31 March 2005 (31.03.2005)

PCT

(10) International Publication Number  
**WO 2005/028342 A1**

(51) International Patent Classification<sup>7</sup>: B65G 17/20,  
47/64

Ingvar [SE/SE]; Djupadal, Nygarden, S-507 71 Gangh-  
ester (SE).

(21) International Application Number:  
PCT/SE2004/001349

(74) Agent: ALBIHNS GÖTEBORG AB; Box 142, S-401 22  
Goteborg (SE).

(22) International Filing Date:  
20 September 2004 (20.09.2004)

(81) Designated States (*unless otherwise indicated, for every  
kind of national protection available*): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:  
0302541-8 22 September 2003 (22.09.2003) SE  
60/481,404 22 September 2003 (22.09.2003) US

(71) Applicant (*for all designated States except US*): ETON  
SYSTEMS AB [SE/SE]; Djupadal, S-507 71 Gangh-  
ester (SE).


(84) Designated States (*unless otherwise indicated, for every  
kind of regional protection available*): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): DAVIDSON, Mats,

[Continued on next page]

(54) Title: PRODUCT CARRIER AND TRANSPORT DEVICE



(57) Abstract: Product carrier, moveable  
along a conveyor track (33, 34) in a conveyor  
arrangement, and designed as a trolley, which has  
two wheel units (3, 4) which are moved along the  
conveyor track. Suspended from each wheel unit  
is a carrier arm (5, 6) for the products that are to be  
conveyed. The carrier arms (5, 6) are connected to  
one another by means of a positioning mechanism  
(9), which maintains a selected essential distance  
(a) between the wheel units (5, 6) regardless of the  
inclination of the track.

WO 2005/028342 A1



European (AT, BE, BG, CH, CY, CZ, DE, **DK**, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, **RO**, SE, SI, SK, TR), OAPI (BF, **BJ**, CF, CG, CI, CM, GA, GN, GQ, GW, ML, **MR**, NE, SN, TD, TG).

(48) Date of publication of this corrected version:

30 March 2006

(15) Information about Correction:

see PCT Gazette No. 13/2006 of 30 March 2006

**Declaration under Rule 4.17:**

— *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*